

P1 1164664

REC'D 14 MAY 2004

WIPO

PCT

# THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office

May 11, 2004


THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/456,794

FILING DATE: March 21, 2003

RELATED PCT APPLICATION NUMBER: PCT/US04/07893

By Authority of the  
COMMISSIONER OF PATENTS AND TRADEMARKS



*T. Wallace*  
T. WALLACE  
Certifying Officer

PRIORITY DOCUMENT  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH  
RULE 17.1(a) OR (b)

BEST AVAILABLE COPY

PATENT APPLICATION SERIAL NO. \_\_\_\_\_

U.S. DEPARTMENT OF COMMERCE  
PATENT AND TRADEMARK OFFICE  
FEE RECORD SHEET

U.S. DEPARTMENT OF COMMERCE  
PATENT AND TRADEMARK OFFICE  
WASHINGTON, D.C. 20530

PTO-1556  
(5/87)

03 24 03

60456794 0323

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.  
 Approved for use through 10/31/2002. OMB 0651-0032  
 U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

# PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).  
 Express Mail Label No. EL 726089273 US

INVENTOR(S)		
Given Name (first and middle [if any])	Family Name or Surname	Residence (City and either State or Foreign Country)
Aaron	Reynolds	106 Cherry Dr., NW., N. Canton, Ohio
Paul	Waterhouse	2145 Governors Road, Canada
Martin	O'Toole	100 Foxhall Dr., Chagrin Falls, Ohio

☒ Additional inventors are being named on the 1 separately numbered sheets attached hereto

## TITLE OF THE INVENTION (500 characters max)

Apparatus for hands-free dispensing of a measured quantity of material

Direct all correspondence to:

☒ Customer Number 26360 CORRESPONDENCE ADDRESS  
 OR, Type Customer Number here

Patent Number  
 26360

☐ Firm or Individual Name

Address

Address

City

Country

State

Telephone

ZIP

Fax

## ENCLOSED APPLICATION PARTS (check all that apply)

☒ Specification Number of Pages 23

☒ Drawing(s) Number of Sheets 9

☐ Application Data Sheet. See 37 CFR 1.76

☐ CD(s), Number

☐ Other (specify)

## METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT

☒ Applicant claims small entity status. See 37 CFR 1.27.

☒ A check or money order is enclosed to cover the filing fees

☒ The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number: 18-0987

☐ Payment by credit card. Form PTO-2038 is attached.

FILING FEE  
 AMOUNT (\$)

\$80.00

The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.

☒ No.

☐ Yes, the name of the U.S. Government agency and the Government contract number are:

Respectfully submitted,

SIGNATURE

*Andrew B. Morton*

Date 03/21/2003

TYPED or PRINTED NAME Andrew B. Morton

TELEPHONE 330-376-1242

REGISTRATION NO.  
 (if appropriate)  
 Docket Number:

37,400

03045

## USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C. 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

60456744.03210.

# **PROVISIONAL APPLICATION COVER SHEET** **Additional Page**

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Approved for use through 10/31/2002. OMB 0651-0032  
 U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE


Docket Number		03045
INVENTOR(S)/APPLICANT(S)		
Given Name (first and middle (if any))	Family or Surname	Residence (City and either State or Foreign Country)
Bruce J.	Van Deman	19101 Van Aken Blvd. #217, Shaker Heights, Ohio

Number 1 of 1

**WARNING:** Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

CERTIFICATE UNDER 37 C.F.R. 1.8(a)

I hereby certify that the foregoing Patent Application submitted herewith for Aaron R. Reynolds, et al., for Apparatus For Hands-Free Dispensing Of A Measured Quantity Of Material, is being deposited with the United States Postal Service as "Express Mail Post Office to Addressee" in an envelope addressed to: Box Provisional Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231, this 21<sup>st</sup> day of March, 2003. Express Mail Label No. EL 726089273 US.



Melinda A. Miller  
Secretary to Andrew B. Morton  
Fourth Floor  
First National Tower  
Akron, Ohio 44308  
(330) 376-1034

Attorney for Applicant  
Aaron R. Reynolds, et al.

# APPARATUS FOR HANDS-FREE DISPENSING OF A MEASURED QUANTITY OF MATERIAL

## RELATED PATENT APPLICATIONS

None.

## BACKGROUND OF THE INVENTION

This invention relates, in general, to devices that discharge a measured quantity of cleaning material in response to a physical input. Moreover, this invention relates to improvements in the operation of the dispenser to facilitate ease of use.

## DESCRIPTION OF THE PRIOR ART

Dispensers, either wall-mounted or stand-alone, are used to hold a quantity of cleaning material, soap, or other disinfecting material. The dispenser is typically positioned near a source of water which is used with the cleaning material to clean the user's hands. When a user needs a quantity of cleaning material, they actuate a lever or a pump so that a quantity of material is dispensed into their hand. Typically, a predetermined amount is dispensed. This can be adjusted by shortening the pump or stroke so that a lesser amount of material is dispensed.

It will also be appreciated that if not enough material is dispensed, the user may actuate the lever additional times to get the amount needed. Additionally, if the container of material is empty, the user will actuate the lever additional times and exert excessive force in an attempt to "squeeze" out the last bits of cleaning material. This applies unnecessary stresses on the actuating lever and associated linkage and, after a period of time, can cause the dispenser to break.

There are various apparatuses that detect the presence of hands or other objects which need to be cleaned and initiate dispensing of water, but not in particular amounts. Examples of such devices are disclosed in the patents to: Yasuo, U.S. Patent No. 5,243,717; Blackmon, U.S. Patent No. 3,576,277; Davies, U.S. Patent No. 4,606,085; Abert et al., U.S. Patent No. 4,946,070; Van Marcke,

U.S. Patent No. 5,086,526; Van Marcke, U.S. Patent No. 5,217,035; Shaw, U.S. Patent No. 5,625,908; Hirsch et al., U.S. Patent No. 5,829,072; and Van Marcke, U.S. Patent No. 5,943,712. It is also known to provide devices with sensors which detect the hand position as it relates to the faucet and adjusts the temperature of the water accordingly. This is generally taught in the patents to 5 Fait, U.S. Patent No. 5,855,356; and the patent to Cretu-Petra, U.S. Patent No. 5,868,311. It is also known to detect the presence of a device and initiate a timing sequence for dispensing materials when multiple users are present, as disclosed in the patent to Gauthier et al., U.S. Patent No. 5,966,753.

10 Various computer-type control devices may be used in the dispensing of materials such as shown in the patent to Pollack, U.S. Patent No. 4,563,780, which discloses a programmable device used by various members of the family to store their water temperature preferences when washing their hands.

15 Although the above described dispensing devices are effective in their stated purpose, it is believed that the mechanisms used to dispense a known quantity of material still exert undue forces on the dispensing mechanism which causes the devices to prematurely wear. Moreover, users who are unfamiliar with the dispensing device may grab or mis-handle the dispensing device looking for a dispensing lever when such does not need to be done. It has been found that most, 20 if not all, automatic dispensing devices do not provide an intuitive indication of where the users are to place their hands or the object to be cleaned so that a dispensed quantity of material may be deposited thereon.

A clear improvement in the aforementioned prior art is disclosed in U.S. Patent No. 6,390,329. This patent, which is assigned to the assignee of the present 25 invention, discloses a hands-free dispensing device which utilizes a unique gearing mechanism to dispense a measured quantity of fluid material. In particular, the disclosed device utilizes an infrared object sensor which detects the presence of an object. Upon detection of this object a motorized pump actuator mechanism converts a motor shaft's rotatable motion into a linear motion which 30 actuates a dispense mechanism which dispenses a predetermined amount of fluid

in a location proximal to the detection zone of the object sensor. Although this device is a clear improvement in the art, it has been found lacking in several regards. First, proper installation of such a device is problematic inasmuch as the infrared sensor, if not properly positioned, will inadvertently actuate the dispensing mechanism and fluid material will accumulate in undesired locations. Additionally, the motorized mechanism does not positively stop at the end of a cycle and as such the gearing contained within the pump actuator mechanism may jam and/or cause the gearing to misalign. Additionally, it has been found that electrical interference between the various components controlling the dispenser and the object sensor may result in misactivation of the pumping mechanism. The device is also lacking in features which facilitate ease of use.

Therefore, it has become apparent that it is desirable to have an apparatus for dispensing a measured quantity of material which provides a positive braking mechanism to ensure proper operation of the dispenser. It is also desirable for this apparatus to be provided with a locating feature to properly install the device so as to preclude inadvertent actuations of the dispensing mechanism. And it is also desirable for the apparatus to be provided with various programming modes to accommodate different types of fluid material and their associated dispensing mechanisms and also to accommodate for the allowance of multiple dosages to be dispensed in the appropriate environment.

### SUMMARY OF THE INVENTION

It has been found, therefore, that an apparatus for hands-free dispensing of measured quantities of fluid material can be provided which improves operation of the known hands-free fluid dispensing devices. In particular, initial positioning of the apparatus is facilitated by use of the object sensor such that prior to permanent installation of the apparatus and loading of the fluid material, the sensor indicates that the device is properly positioned for use. In other words, the infrared sensor sends out a test signal and if the apparatus is temporarily



positioned in an undesirable location indicia will turn off to indicate to the installer that this position is not appropriate. Accordingly, the installer will move the device to another position for location testing. If the lights at this time turn on then the installer knows that this is an appropriate position for the infrared sensor and that installation of the device is proper in the position selected. Upon completion of the installation of the device the apparatus is loaded with a container of fluid material connected to a dispensing mechanism which deposits a measured quantity of material when the presence of an object is detected and without the user having to actuate a push bar or lever.

In the initial setup procedure of the dispensing apparatus, the installer may select among at least three different program modes. In the first program mode the user may activate or deactivate a plurality of LEDs or lighting indicia which instruct the end-user of the device as to the proper positioning of their hand or other object to be in a position to receive a dispensed quantity of fluid material. Accordingly, the installer may select whether to provide this lighting indicia or not. In a second program mode, the end-user may select a dosage size. For example, the installer may select one, two or three cycles of operation depending upon the nature of the installed environment. In a final programming mode, the installer may select the dispenser size for the type of fluid which is to be dispensed. It will be appreciated that the amount of fluid dispensed for lotions is different than the amount of fluid dispensed for soaps and the like. Accordingly, after conclusion of these various modes and installation of the designated fluid, the object sensor is enabled and an associated processor will calculate the amount of usage anticipated for that particular fluid dispensing device. Accordingly, upon reaching a predetermined use level, typically about 95%, an alert signal is generated to indicate to the user that the fluid material needs to be replaced.

It will be appreciated that the device may be provided with additional circuitry features to facilitate its operation. Accordingly, a control circuit with an overload circuit may be provided such that any detection of gear jamming or other malfunctions of the gearing mechanism will generate a signal that is received by a

processor to stop operation of a motor that actuates a dispense mechanism and precludes any further damage to the device. Yet another feature that may be provided by the control circuit of the fluid dispenser is a braking circuit which automatically turns the motor off at the end of a dispense cycle to prevent its coasting so as to ensure the proper positioning of the gears and related mechanisms. Still yet another feature of the device is the separation of various components within the control circuit such that the infrared sensor which is used to detect the object is isolated from other circuitry components. Accordingly, this feature substantially minimizes false activations of the dispense mechanism so as to reduce unwanted usage.

Accordingly, use and operation of an apparatus for hands-free dispensing of a measured quantity of material, as described above, becomes the principal object of this invention with other objects thereof becoming more apparent upon a reading of the following brief specification considered and interpreted in view of the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a side elevational cross-sectional diagram of the apparatus;

FIGURE 2 is a front perspective view of a pump actuator mechanism employed in the apparatus;

FIGURE 3 is a top plan view of a spur gear employed in the pump actuator mechanism;

FIGURE 4 is a cross-sectional view, taken substantially along line 4-4 of FIGURE 3, of the spur gear;

FIGURE 5 is a bottom plan view of the spur gear employed in the pump actuator mechanism;

FIGURE 6 is a rear perspective view of the spur gear;

FIGURE 7 is a rear perspective view of the pump actuator mechanism;

FIGURE 8 is a front perspective view of an actuator gear employed in the pump actuator mechanism;

FIGURE 9 is a side elevational view of the actuator gear;

FIGURE 10 is a bottom elevational view of the actuator gear;

FIGURE 11 is an elevational view of a front panel of the apparatus;

5      FIGURE 12 is an elevational view of alternative indicia configuration of the front panel;

FIGURE 13 is an operational flow chart set up and programming mode steps utilized by the apparatus according to the present invention; and

FIGURE 14 is a schematic diagram of the control circuit employed by the apparatus of the present invention.

## 10      **BRIEF DESCRIPTION OF THE PREFERRED EMBODIMENTS**

FIGURE 1 depicts an apparatus or dispenser, generally designated by the numeral 10, for dispensing a measured quantity of material as a result of hands-free actuation. The dispenser 10, which may be a wall-mounted or a stand-alone device, includes a housing 14 having a back shell 16 mateable with a front shell 18. In the preferred embodiment, the back shell 16 and the front shell 18 are connected by a hinge 20 at an underside of the dispenser 10. If desired, the hinge mechanism may be placed on either side of the dispenser 10 or at its top. A key latch 22 is provided at the side opposite of the hinge 20 so as to hold the front shell 18 in a mated position with the back shell 16. This encloses the device and precludes its access by unauthorized personnel. Although a key latch is shown, it will be appreciated that other mechanisms for latching the two shells 16 and 18 to one another may be employed. The shells 16 and 18 are preferably manufactured of a rigid plastic material which maintains its appearance, is easy to manufacture, and easily withstands day-to-day use.

25      A battery compartment, designated generally by the numeral 26, is carried by an interior surface of the housing 14. The battery compartment 26, in the preferred embodiment, carries eight AA batteries. The batteries are employed to operate various features of the dispenser as will become apparent from the

discussion below. Of course, other battery sizes and quantities could be employed. Alternatively, an AC power source or the like could be used.

5 A dispense mechanism, which is generally designated by the numeral 28, is carried by a plate 29. The hinge 20 carries the plate 29 such that when the front shell 18 is opened, the dispense mechanism 28 remains supported by the plate 29. The dispense mechanism 28 may be one commonly available in the art or, in the preferred embodiment, is like the one disclosed in U.S. Patent Application Serial No. 09/397,314 filed on September 16, 1999, and which is assigned to the Assignee of the present invention and which is incorporated herein by reference.

10 The dispense mechanism 28 incorporates a pump dome valve 32 which, when pressed, dispenses a measured quantity of fluid material carried by a fluid material container 36. The dispense mechanism 28 is coupled to the container 36 via a connector 37. The container 36 is a replaceable unit as is well known in the art. When the pump dome valve 32 is actuated, the material is dispensed via a nozzle

15 34 through an opening 38 in a bottom portion of the front shell 18 into the user's hand, as will be described in detail below. The fluid material container 36 may contain soap, disinfectant, or other fluid material that is dispensable through the pump mechanism 28. Ideally, the container 36 will carry 1,000 mL of fluid material product. The dispense mechanism 28 typically deposits or dispenses 1.5

20 mL of product per cycle. Of course, the container 36 may be different sizes. And the dispense mechanism may dispense different quantities.

A pump actuator mechanism, which is generally shown in FIGURE 1 and which is shown in detail in FIGURES 2-10, and generally designated by the numeral 40, includes an infrared sensor 42. The infrared sensor is positioned at an

25 area near the opening 38 of where the dispense mechanism 30 deposits the material. The infrared sensor detects the presence of an object, such as a user's hand or other object to be cleaned, and cycles the pump actuator mechanism 40 to dispense a measured quantity of fluid material. The infrared sensor 42 includes an emitter and receiver to detect the presence of a user's hand or other object. Of

30 course, other commercially available sensors which detect the presence of an

object, without direct physical contact, and generate a corresponding actuation signal may be employed in the present invention.

5 The pump actuator mechanism 40 is carried in an assembly housing 46 which is replaceably mounted to the interior of the front shell 18 such that when the front shell is hingedly opened, the assembly housing 46 moves in a like manner. Carried in the assembly housing 46 is a motor 48 which is powered by the batteries carried in the battery compartment 26. The motor has a rotatable shaft 50 extending therefrom with a worm gear 52 at one end. The worm gear 52 operatively drives a differential gear assembly 54 in a manner well known in the art. Briefly, the purpose of the differential gear assembly is to significantly reduce the speed of the motor output so that the dispensing of the material can be easily controlled. Alternatives for imparting a force to the differential gear assembly could be provided by a piston or solenoid configuration.

10 The differential gear assembly 54 converts the initial high-speed rotation of the motor shaft to a more manageable rotational speed that can then be converted into a linear motion that repeatably engages the dispense mechanism 30. The differential gear assembly 54 includes three spur gears 56, 58, and 60. The worm gear 52 contacts a plurality of outer teeth 62 of the first spur gear 56. The spur gear 56 also includes a plurality of inner teeth 64 that mesh with a plurality of outer teeth 66 extending from the periphery of the second spur gear 58. In a like manner, a plurality of inner teeth 68 of the spur gear 58 engage a plurality of outer teeth 70 of the spur gear 60. As those skilled in the art will appreciate the rotational velocity of the spur gear 60 is significantly reduced by the interconnecting gears 56 and 58.

15 As best seen in FIGURES 1 and 3-6, the spur gear 60 includes a plate 74 with radially disposed slots 76 extending therethrough and positioned in about 120° increments. It will be appreciated that the number of slots and their position can be varied as needed. Extending from the plate 74 in one direction is a hub 80 from which further extends a nub 82. The nub 82 is received in an indentation 83 in one side of the assembly housing 46 so as to rotatably receive and align the gear

60. This assists in the uniform and efficient rotation of the gear 60 which, in turn, ensures the effective operation of the mechanism 40.

5 An axial stem 86 may concentrically extend from a bottom surface of the hub 80 toward the plate 74. Disposed between an interior wall of the hub 80 and the axial stem 86 is a hub cam, generally designated by the numeral 90. The hub cam 90 is concentrically disposed around the stem 86.

10 The hub cam 90 includes a plurality of hub ramps 92, wherein each hub ramp is provided with an alphabetic suffix designation (a, b, or c in the drawings). Although three hub ramps 92 are shown, it will be appreciated by those skilled in the art that one, two, or more ramps may be provided, depending upon the desired pumping action. The hub ramps 92 are essentially identical in construction and their various features are also provided with a corresponding alphabetic designation. Each hub ramp 92 includes an outer wall 94 which is concentrically adjacent the interior wall of the hub 80, and an inner wall 96 which is concentrically adjacent the axial stem 86. The outer walls may be integral with the interior hub wall, or they may be spaced apart from the wall, as shown. Likewise, the inner walls may be spaced apart from the axial stem, or they may be integral, as shown. The outer wall 94 and the inner wall 96 are connected at one end by a trailing wall 98 and at the opposite end by a leading wall 100. Each of these walls -- 94, 96, 98, and 100 -- are connected by a cam surface 102 which angularly extends from the trailing wall 98 to the leading wall 100. The leading wall 100 is of minimal height at the bottom of the hub. The cam surface 102 rises up from the leading wall 100 and extends to the trailing wall 98. The top of the trailing is at about a mid-point position between the bottom of the hub 80 and the plate 74.

25 In order to convert the rotational motion of the motor shaft 50, an actuator gear, generally designated by the numeral 110, is slidably received within the hub 80. The actuator gear 110 is also slidably captured within the housing 46, as seen in FIGURE 7. Accordingly, the actuator gear 110 is moveable into and out from the assembly housing to actuate the dispense mechanism 30.

The actuator gear 110, as best seen in FIGURES 8-10, includes a sleeve 116 which has a partially enclosed end 118 with a hole 120 therethrough. The hole 120 slidably fits over the axial stem 86 for alignment and positioning purposes. Opposite the partially closed end, the sleeve has a rim 124 that forms an open end 122. Extending outwardly from the partially closed end 118 is a sleeve cam 126 which coacts with the hub cam 90. The sleeve cam 126 includes a plurality of sleeve ramps 130 which have alphabetic suffix designations for each of the ramps provided. The number of ramps provided correspond to the number of ramps provided by the hub cam 90. Each sleeve ramp 130 includes an outer wall 132 and an inner wall 134. The outer and inner wall are joined by a leading wall 136 and a trailing wall 138. Each ramp 130 provides a cam surface 140 that interconnects the outer, inner, leading, and trailing walls.

Initially, the actuator gear 110 is primarily received within the hub 80. Accordingly, the trailing walls 98 align with the leading walls 136 in a resting position. When the sensor 42 detects an object and initiates the pump actuator mechanism 40, the gear 60 rotates and the camming action upon the actuator gear 110 is initiated. As this happens, the rim 124 moves axially outwardly from the plate 74 and compresses the dome valve 32. This continues until the trailing walls 98 are aligned with the trailing walls 138. At which time, due to the resiliency of the pump dome valve 32, the actuator gear 110 falls back into the hub and the rim 124 returns to its original position. Alternatively, instead of relying on the resiliency of the dome, the actuator gear could be returned to its initial position by use of additional gearing or by spring biasing. In any event, reciprocating motion of the actuator gear 110 cycles the dispense mechanism 30.

In order to maintain alignment and to hold the actuator gear 110 within the housing, the sleeve 116 includes a pair of opposed flats 144. Each flat 144 extends from the rim 122 to a stop plate 146. The housing 46 has a rounded-slot 148 that slidably receives a portion of the actuator gear 110. In particular, the flats 144 extend through the slot 148, while the interior of the housing 46 bears against the stop plates 146 when the gear 110 is fully extended. This precludes the

actuator gear 110 from falling out of the housing and ensures that the actuator gear 110 remains in place and is returnable to a starting position to initiate additional operating cycles.

5 A sensor 151 is provided in the assembly housing 46 and is alignable with the slots 76 and the plate 74. Accordingly, as the sensor 151 detects the passing of the slot 76, the sensor instructs the motor to stop rotation. This ensures that only one actuating of the dispensing mechanism occurs for each detection of a hand or object to be cleaned underneath the sensor 42. Of course, the sensor 151 could be situated or programmed to allow for passage of two or more slots 76 to allow for multiple cycling of the dispense mechanism 30. The sensor 151 could be an infrared type that detects interruption of an infrared beam. A magnetic proximity switch or a monitored timer could also be used to detect gear position.

10 The pump actuator mechanism 40 includes a control circuit 152 which utilizes the power generated from the batteries to illuminate a series of light emitting diodes 156, 158, and 160 that are viewable through a panel 162 on the front shell 16. The panel, as seen in FIGURE 11, is provided with indicia adjacent the LEDs to assist the user. In the preferred embodiment, the panel provides downwardly pointing triangles 163. These LEDs may be any color but are preferably green in color and may be sequenced to illuminate in a manner which indicates the direction in which the user must place their hand to activate the sensor 42. For example, the top LED 156 is illuminated first and then followed in rapid succession by LEDs 158 and 160. After a predetermined delay, the lighting sequence starts over. Moreover, other shapes or combinations of dissimilar shapes could be used in place of the triangles 163. See, for example, FIGURE 12.

20 Although three LEDs are shown, it will be appreciated that two or more LEDs may be provided. Also provided in a viewable area of the front shell is a low battery indicia LED 164 which, when illuminated, indicates that the batteries are running low. A low fluid indicia LED 165 is illuminated when a calculation performed by the control circuit 152 determines that the container 36 needs to be

25



replaced. The LEDs 164 and 165 may be any color, but preferably they are red and yellow, respectively.

Also provided in an area near the LEDs is a "smart" or hidden switch 168. Location of this switch is typically only known by housekeeping personnel and is depressed so as to disable the sensor 42 for a predetermined time period, *e.g.*, one minute. This allows the housekeeping personnel to clean underneath the dispenser without activating the dispensing mechanism during that time. Opening of the front shell 18 also removes the coupling between the pump actuator mechanism 40 and the dispense mechanism 28. In this position, actuation of the sensor 42 will not cause inadvertent dispensing of material.

Other features which may be added to the dispenser are timing mechanisms which emit an audible tone when the dispenser is cycled. A 20-second timer then emits another tone to indicate that a washing event may be completed. Also, the dispenser may be provided with an AC adapter so as to eliminate the need for battery power. Yet another feature of the present invention is that a malfunctioning pump actuator mechanism or dispense mechanism may be easily replaced by opening the front shell and removing the appropriate fasteners and then installing a new unit.

Referring now to FIGURE 13, installation and set-up of the dispenser 10 is described in detail. It will be appreciated that the installation procedure 200 is separated into a set-up procedure designated generally by the numeral 202 and a program procedure generally indicated by the numeral 204. Implementation of these procedures 202, 204 is facilitated by operation of the control circuit 152, the components of which will be described in detail below. In any event, the set-up procedure 202 starts at step 206 wherein the installer will connect an appropriate power source to the control circuit 152 at step 206. This may include the installation of batteries into the battery compartment 26 or connection of a power supply in the event batteries are not utilized. At step 208 the sensor 42 is automatically enabled and functions as previously described and the LEDs 156-160, or other signaling mechanism begin to flash repeatedly. Of course other

indicators of proper positioning could be employed such as auditory signals, vibrations, written indicia on a liquid crystal display, utilizing a different sequencing of lights to name just a few.

5        At step 210, prior to loading a container of fluid, the installer positions the housing 14 in a preferred location. Typically this location will be near a sink if the dispenser is used to dispense soap. However, the dispenser may be positioned elsewhere in convenient locations such as in a restaurant, hospital or other facility where sanitizing lotions are to be dispensed or, in the alternative, where moisturizing lotions are to be dispensed. In any event, the positioning of the  
10       housing 210 is critical inasmuch as the sensor needs to be positioned in an area where it is not inadvertently triggered. If such an event were to occur, the fluid contained within the dispenser would be dispensed without anyone to collect the dispensed material. Accordingly, if the infrared sensor falsely detects the presence of an object when in fact no object is present its material may be  
15       automatically dispensed resulting in waste and a mess. When the infrared sensor is placed in a preliminary position and if the infrared sensor detects an object when in fact the installer knows that object is not a proper object to actuate the dispenser, then the plurality of LEDs, such as the LEDs 156, 158 and 160, will stop flashing repeatedly at step 212. If this occurs, the installer will then know to  
20       re-position the housing at step 210. This repositioning step is repeated until the LEDs flash repeatedly. When the LEDs flash repeatedly the sensor is in a position to detect an object that is specifically placed in the zone of receiving a dispensed fluid. At step 214, the installer will then permanently secure the housing in a position where the LEDs are flashing.

25       Various features may be implemented upon securement of the dispensing device. In order to implement these programmed procedures, the smart or hidden button 168 is actuated at step 220. This temporarily disables the infrared sensor at step 222 so that undesired actuation of the dispense mechanism does not occur. At this time, at step 224 the installer may select from three program modes.

In a first mode, at step 226, the installer is allowed to select dosage sizes of one, two or three cycles at step 228. This allows the installer to properly size the amount of fluid to be dispensed depending upon the location of the unit. For example, a preschool installation would only require a one cycle dispensing to take place. In contrast, a garage or factory setting would typically require a three cycle dispensing operation to take place in view of the large amount of soap typically required to clean ones hands in such an environment. An in-between two cycle selection may also be provided. Although only three cycles of operation are allowed for selection in the preferred embodiment it will be appreciated that any number of dispensing cycles may be programmed. Upon completion of step 228 the process continues to the exit program mode at step 238.

If mode 2 is selected at step 230, the installer is allowed to select the dispenser size at step 232. The dispenser size 232 is associated with the type of material to be installed in the dispensing unit. Typically 1.0 ml of fluid is dispensed if the fluid is a moisturizer. Alternatively, 1.25 ml may be dispensed if the fluid is a sanitizer. And, 1.5 ml of fluid is dispensed if the fluid is a soap. Upon selection of the dispenser size the program continues to the exit program mode at step 238.

In mode 3, performed at step 234, the installer will select whether to turn on or off the directional LEDs at step 236. These directional LEDs are utilized to indicate to the end-user where to place their hand or other object which is to receive the dispensed fluid. Accordingly, if it is desired to extend battery life by not illuminating the directional LEDs, they may be turned off. Or, if the end-user desires to have the LEDs turned on, for example, in a preschool environment to ensure that the dispensing device is properly used, then the LEDs may be turned on. Upon completion of step 236, the program proceeds to the exit program mode step at step 238.

Upon completion of step 238, the procedure continues to step 240 whereupon the installer will install the bag of fluid material at step 240. This

indicates to the sensor that it may now be enabled at step 242. Immediately upon installation of the bag 240 and enablement of the sensor 242 an estimated number of cycles is calculated based upon the dose cycle selected at step 228 and the dispenser size selected at step 232. Based upon a predetermined limit of usage, for example, after 95% of the material is depleted, a low fluid indicator is illuminated. This indication will advise the end-user that the fluid container is likely to be fully exhausted in the near future and that it should be replaced.

Referring now to FIGURE 14, it can be seen that the control circuit utilized for implementing the aforementioned procedures is generally indicated by the numeral 152. The control circuit 152 includes a sensor circuit designated generally by the numeral 300 and a systems circuit designated generally by the numeral 302. The sensor circuit 300 includes primarily just the infrared sensor 42 for reasons which will become apparent as the description proceeds.

The system circuit 302 includes the smart/hidden switch 168, the light emitting diodes 156-165, an overload circuit 304 and a processor 306. Those skilled in the art will appreciate that the processor 306 includes the necessary hardware, software and memory required to implement the aforementioned programming procedures and generally operate the components associated with the dispenser 10. Both the sensor circuit 300 and the overload circuit 304 include a respective backplane shield 310 and backplane shield 312 as indicated so as to isolate any radio frequency signals that may inadvertently activate the infrared sensor 42. In other words, it has been determined that the dispenser operates much more efficiently by separating out the circuit components associated with the sensor 42 from the other components associated with the control circuit 152. Although the sensor circuit 300 still communicates with the processor 306 for operational implementation it is isolated as much as possible to preclude interference from the system circuit 302 that may adversely trigger actuation of the sensor and thus cause an unwanted dispensing event.

The system circuit 302 includes an overload circuit 304 which requires a logic level pulse to start the operation of the motor contained within the pump

actuator 40. When the motor is running, diodes D10A and D10B measure the voltage drop across the driving MOSFET Q3. If the voltage drop exceeds a predetermined value such as 0.5 volt, an overload signal is generated by turning transistor Q16 on. In the present instance, the overload signal is operatively received by the microprocessor 306. Once the microprocessor 306 detects the overload signal, the processor generates a signal to turn the pump actuator 40 and thus the dispense mechanism 28 off and alerts the end-user by flashing a red light emitting diode selected from one of the LEDs 156-165. Accordingly, the overload circuit functions to detect jamming or other problems associated with the pump actuator or dispense mechanism and provides for indicating such problems to the processor which relays a system problem to the end-user. Accordingly, fluid is not dispensed and problems associated therewith are averted.

Yet another feature of the control circuit 152 is the utilization of a brake circuit which quickly stops the rotation of the electric motor shaft provided by the pump actuator 40. It will be appreciated that upon normal actuation of the motor it cycles through an operation and although an enabling signal is withdrawn from the motor, the motor shaft may continue to rotate a minimal amount. Over a period of time these additional movements of the motor shaft may cause gears within the pump actuator 40 to jam and cause related problems. Additionally, these over rotations may increase the number of dispense cycles and result in a miscalculation of the number of dispensing cycles which in turn causes the low level indicator to activate prematurely. Alternatively, output from the sensor 151, which is preferably an opto-isolator may be used to initiate brake input. In any event, the brake circuit is intended to quickly stop and prevent the over-rotation of the electric motor shaft. In order to initiate the braking process a logic level pulse on the brake input line associated with the ground of MOSFET Q2 is utilized. When this input is received, the MOSFET Q2 is activated initiating the brake by connecting the motor drive and brake output terminal to ground, effectively braking the motor to a stop. Accordingly, upon receipt of the braking signal the

motor is positively stopped at a precise location so as to preclude jamming or other problems associated with over-rotation of the motor shaft.

5 It is apparent then from the above description of the structure and operation of the dispenser 10 that the problems and shortcomings associated with previous dispensing mechanisms have been overcome. In particular, the dispenser 10 now provides a device which provides programming features that facilitate the dispensing of different types of fluids and allows for different dosage of fluids to be dispensed. Additionally, the control circuit 152 has been improved to preclude activations of the dispensing device. Further misactivations are prevented by  
10 isolating the infrared sensor from most all other circuitry associated with the device. Additionally, the present invention provides for an installation procedure which indicates to the installer a preferred location of the dispensing mechanism so as to preclude inadvertent dispensing events. Circuitry improvements are also disclosed which facilitate the effective operation of the dispensing mechanism.

15 While a full and complete description of the invention has been set forth in accordance with the dictates of the Patent Statutes, it should be understood that modifications can be resorted to without departing from the spirit hereof or the scope of the appended claims.

20 For example, the invention has been described in the context of a dispensing mechanism for cleaning hands. However, it is apparent that the structure and operational methods of the apparatus could easily be adapted for dispensing any type of fluid material that is initiated or cycled by actuation of a touchless sensor.

What is claimed is:

- 1       1. Apparatus for automatically dispensing a fluid comprising:
  - 2           a) a container adapted to carry a supply of fluid;
  - 3           b) a valve connected to said container, wherein actuation of said valve
  - 4               dispenses the fluid;
  - 5           c) an apparatus position indicator proximally associated with said
  - 6               container;
  - 7           d) an object sensor positioned near said valve, wherein said object sensor
  - 8               monitors an area below where said valve dispenses when open and
  - 9               upon detection of an object opens said valve; and
  - 10          e) wherein initial positioning of the apparatus triggers said apparatus
  - 11               position indicator to generate an appropriate signal until said object
  - 12               sensor is properly positioned.
- 1       2. The apparatus according to Claim 1, wherein said position apparatus
- 2           indicator includes at least one illumination device that illuminates when said
- 3           object sensor is properly positioned.
- 1       3. The apparatus according to Claim 1, wherein said position indicator includes
- 2           at least one illumination device that illuminates until said object sensor is
- 3           properly positioned.
- 1       4. A method for installing an automated fluid dispenser, comprising:
  - 2           a) providing a fluid dispenser for carrying a container, a valve connected
  - 3               to said container wherein actuation of said valve dispenses a fluid
  - 4               carried by said container when installed, an apparatus position
  - 5               indicator carried by said fluid dispenser, and an object sensor
  - 6               positioned near said valve;

- 1           b) connecting a power source to at least said apparatus position indicator
- 2           and said object sensor;
- 3           c) positioning said fluid dispenser in at least one prospective mounting
- 4           location;
- 5           d) emitting from said object sensor a test signal to ensure proper
- 6           positioning of said fluid dispenser; and
- 7           e) repeating steps c) and d) until said apparatus position indicator
- 8           provides a positive indication of said fluid dispenser's placement.

- 1           5. The method according to Claim 2, further comprising:
- 2           marking a position of said fluid dispenser's positive placement; and
- 3           permanently installing said fluid dispenser at said position.

- 1           6. The method according to Claim 5, further comprising:
- 2           installing said container in said fluid dispenser.

- 1           7. Apparatus for dispensing a measured quantity of fluid, comprising:
- 2           a) an object sensor;
- 3           b) a container carrying a supply of fluid;
- 4           c) a dispense mechanism coupled to said container to control an amount
- 5           of fluid to be dispensed;
- 6           d) a pump actuator mechanism coupled to said object sensor, wherein
- 7           detection of an object by said object sensor cycles said pump actuator
- 8           mechanism to engage said dispense mechanism which dispenses a
- 9           measured quantity of fluid and wherein said pump actuator mechanism
- 10          converts rotational motion to linear motion to cycle said dispense
- 11          mechanism; and
- 12          e) a hidden switch carried by said container, wherein actuation of said
- 13          hidden switch enables a processor to enter a program mode.



1 8. The apparatus accordingly to Claim 7, further comprising:  
2 at least one illuminating indicia connected to said processor wherein  
3 entry into said program mode is indicated by said at least one illuminating  
4 indicia.

1 9. The apparatus according to Claim 8, further comprising:  
2 at least two lights, wherein said lights are sequentially illuminated to  
3 indicate where an object should be placed for receipt of the fluid; and  
4 wherein entry into said program mode allows enablement or  
5 disablement of said at least two lights.

1 10. The apparatus according to Claim 8 wherein entry into said program mode  
2 allows selection of a number of cycles of said pump actuator mechanism to  
3 control an amount of dispensed fluid upon detection of an object.

1 11. The apparatus according to Claim 8 wherein entry into said program mode  
2 allows selection of a size of said dispense mechanism.

1 12. The apparatus according to Claim 8, further comprising:  
2 a low level indicator connected to said processor,  
3 wherein entry into said program mode allows selection of a number of  
4 cycles of said pump actuator mechanism to control an amount of dispensed  
5 fluid upon detection of an object,  
6 wherein entry into said program mode allows selection of a size of said  
7 dispense mechanism, and  
8 wherein said processor calculates when the fluid in a given size of  
9 container will be depleted to a predetermined level based upon said number  
10 of cycles and size of said dispense mechanism.

- 1 13. Apparatus for dispensing a measured quantity of fluid, comprising:  
2 a) an object sensor which generates an object signal upon detection of an  
3 object;  
4 b) a container carrying a supply of fluid;  
5 c) a dispense mechanism coupled to said container to control an amount  
6 of fluid to be dispensed;  
7 d) a pump actuator mechanism coupled to said object sensor, wherein  
8 detection of an object by said object sensor cycles said pump actuator  
9 mechanism to engage said dispense mechanism which dispenses a  
10 measured quantity of fluid and wherein said pump actuator mechanism  
11 converts rotational motion to linear motion to cycle said dispense  
12 mechanism; and  
13 e) a control circuit having a processor to receive said object signal,  
14 wherein said processor generates a cycle signal received by said pump  
15 actuator mechanism to actuate said dispense mechanism.

- 1 14. The apparatus according to Claim 13, further comprising:  
2 a motor carried by said pump actuator mechanism, wherein a motor  
3 drive input signal is generated by said processor;  
4 a motor sensor coupled to said pump actuator, said motor sensor  
5 detecting a position of said motor and generating a brake input signal when  
6 said motor position is detected,  
7 wherein generation of said brake input signal connects said motor  
8 drive input signal to ground to effectively brake said motor.

- 1 15. The apparatus according to Claim 13, further comprising:  
2 a motor carried by said pump actuator mechanism, wherein a motor  
3 drive signal is generated by said processor to actuate said motor and said  
4 pump actuator mechanism;

1 an overload circuit carried by said control circuit, wherein if said  
2 overload circuit detects a voltage value in excess of a predetermined  
3 threshold, an overload signal is generated and received by said processor  
4 which in turn stops generation of said motor drive signal.

1 16. The apparatus according to Claim 13, wherein said control circuit  
2 comprises:


3 a sensor circuit for carrying said object sensor; and

4 a systems circuit for carrying said processor, wherein said sensor  
5 circuit and said systems circuit are maintained on their own respective  
6 circuit boards to minimize interference therebetween.

1 17. The apparatus according to said Claim 16, wherein each said respective  
2 circuit board functions as a shielded backplane.

**ABSTRACT OF THE DISCLOSURE**

5 An apparatus for automatically dispensing a fluid includes a container adapted to carry a supply of fluid, and a valve connected to said container, wherein actuation of said valve dispenses the fluid. Also included is an apparatus position indicator proximally associated with the container and an object sensor positioned near the valve. The object sensor monitors an area below where the valve dispenses when open and upon detection of an object opens said valve. Initial positioning of the apparatus triggers the apparatus position indicator to generate an appropriate signal until said object sensor is properly positioned. Once positioned the device may be permanently secured. A control circuit within 10 the apparatus also allows programming of lighting indicators, dispense cycle size, and dispense quantities. The control circuit also provides for overload protection, motor braking and RF shielding.



Apparatus for hands-free dispensing of a measure quantity of material  
Aaron R. Reynolds, et al.  
Atty. docket # 03045








FIG. 2















FIG. 7








Fig. 13




Fig. 14

This Page is inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record

## BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLORED OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images  
problems checked, please do not report the  
problems to the IFW Image Problem Mailbox**